

Description

AS5169D02L Threaded Plug

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AS5169D02L
Minimum Qty (MOQ):	2
NSN:	5365-00-726-4161
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



NO IMAGE
AVAILABLE

P/N AS5169D02L Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Thread Length:	0.328 Inches Nominal External
Head Height:	0.250 Inches Nominal
Overall Length:	0.594 Inches Nominal
Unable To Decode:	Unable To Decode
Connection Style:	Plain
Body Core Diameter:	0.062 Inches Nominal
Core Depth:	0.250 Inches Minimum And 0.266 Inches Maximum
Bleeder Hole Center To Threaded End Distance:	0.125 Inches Minimum And 0.188 Inches Maximum
Bleeder Hole Diameter:	0.063 Inches Nominal
Nominal Thread Size:	0.312 Inches External
Seat Angle:	45.0 Degrees
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Style Designator:	Plug, Machine W/bleeder Holes
Thread Series Designator:	Unf External

How to Order

Order this threaded plug from our inventory online by visiting <https://military-fasteners.com/fittings/fitting/AS5169D02L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.