

**Description**

outer diameter: 5/16", thread: 1/2-20, aluminum, with lockwire holes, port plug and bleeder, New Revision, AS5169 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AN814-5DL](#)

|                         |                              |
|-------------------------|------------------------------|
| SKU / Model:            | AS5169D05L                   |
| Minimum Qty (MOQ):      | 5                            |
| NSN:                    | 5365-00-124-3042             |
| ECCN:                   | EAR99                        |
| National Motor Freight: | 013120, Aluminum Article Noi |



\* See page 2 for technical characteristics

## P/N AS5169D05L Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a External   |
| <b>Thread Direction:</b>                              | Right-hand External   |
| <b>Thread Length:</b>                                 | 0.297 Inches Nominal External   |
| <b>Head Height:</b>                                   | 0.250 Inches Nominal  |
| <b>Overall Length:</b>                                | 0.656 Inches Nominal  |
| <b>Unable To Decode:</b>                              | Unable To Decode  |
| <b>Connection Style:</b>                              | Plain   |
| <b>Body Core Diameter:</b>                            | 0.234 Inches Nominal  |
| <b>Core Depth:</b>                                    | 0.281 Inches Nominal  |
| <b>Bleeder Hole Center To Threaded End Distance:</b>  | 0.188 Inches Nominal  |
| <b>Bleeder Hole Diameter:</b>                         | 0.062 Inches Nominal  |
| <b>Nominal Thread Size:</b>                           | 0.500 Inches External   |
| <b>Material:</b>                                      | Aluminum Alloy 7075 Overall Or Aluminum Alloy 2014 Overall  |
| <b>Material:</b>                                      | Aluminum Alloy 7075 Or Aluminum Alloy 2014 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-268,t6 Fed Spec 1st Material Response Overall Or Qq-a-268,t851 Fed Spec 1st Material Response Overall Or Qq-a-266 Fed Spec 2nd Material Response Overall |
| <b>Material Document And Classification:</b>          | Qq-a-268,t6 Fed Spec 1st Material Response Or Qq-a-268,t851 Fed Spec 1st Material Response Or Qq-a-266 Fed Spec 2nd Material Response Overall                 |
| <b>Surface Treatment:</b>                             | Anodize Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall  |
| <b>Style Designator:</b>                              | Plug, Machine W/bleeder Holes   |
| <b>Thread Series Designator:</b>                      | Unf External  |

## How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169D05L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.