

Description

tube outer diameter: 1/2", thread: 3/4-16, aluminum - with lockwire holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN814-8DL](#)

SKU / Model:	AS5169D08L
Minimum Qty (MOQ):	5
NSN:	5365-00-278-8804
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N AS5169D08L Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Thread Length:	0.375 Inches Nominal External
Head Height:	0.312 Inches Nominal
Overall Length:	0.781 Inches Nominal
Unable To Decode:	Unable To Decode
Connection Style:	Plain
Body Core Diameter:	0.390 Inches Nominal
Core Depth:	0.360 Inches Nominal
Bleeder Hole Center To Threaded End Distance:	0.250 Inches Nominal
Bleeder Hole Diameter:	0.062 Inches Nominal
Head Core Diameter:	0.750 Inches Nominal
Head Type:	Cored
Nominal Thread Size:	0.750 Inches External
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
Style Designator:	Plug, Machine W/bleeder Holes
Thread Series Designator:	Unf External

How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169D08L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.