

**Description**

outer diameter: 1", thread: 1-5/16-12, aluminum

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[AN814-16D](#)

|                         |                                    |
|-------------------------|------------------------------------|
| SKU / Model:            | AS5169D16                          |
| Minimum Qty (MOQ):      | 2                                  |
| NSN:                    | 5365-00-287-0098                   |
| ECCN:                   | EAR99                              |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



\* See page 2 for technical characteristics

## P/N AS5169D16 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                                 | 3a External                                   |
| <b>Thread Direction:</b>                             | Right-hand External                           |
| <b>Thread Length:</b>                                | 0.469 Inches Nominal External                 |
| <b>Head Height:</b>                                  | 0.406 Inches Nominal                          |
| <b>Overall Length:</b>                               | 1.000 Inches Nominal                          |
| <b>Connection Style:</b>                             | Plain   |
| <b>Body Core Diameter:</b>                           | 0.843 Inches Nominal                          |
| <b>Core Depth:</b>                                   | 0.406 Inches Minimum And 0.422 Inches Maximum |
| <b>Bleeder Hole Center To Threaded End Distance:</b> | 0.406 Inches Minimum And 0.438 Inches Maximum |
| <b>Bleeder Hole Diameter:</b>                        | 0.062 Inches Nominal                          |
| <b>Thread Quantity Per Inch:</b>                     | 12 External                                   |
| <b>Nominal Thread Size:</b>                          | 1.312 Inches External                         |
| <b>Seat Angle:</b>                                   | 45.0 Degrees                                  |
| <b>Material:</b>                                     | Aluminum Alloy Overall                        |
| <b>Surface Treatment:</b>                            | Anodize Overall                               |
| <b>Style Designator:</b>                             | Plug, Machine W/bleeder Holes                 |
| <b>Thread Series Designator:</b>                     | Un External                                   |

## How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169D16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.