

Description

outer diameter: 1", thread: 1-5/16-12, aluminum

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN814-16D](#)

SKU / Model:	AS5169D16
Minimum Qty (MOQ):	2
NSN:	5365-00-287-0098
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N AS5169D16 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Thread Length:	0.469 Inches Nominal External
Head Height:	0.406 Inches Nominal
Overall Length:	1.000 Inches Nominal
Connection Style:	Plain
Body Core Diameter:	0.843 Inches Nominal
Core Depth:	0.406 Inches Minimum And 0.422 Inches Maximum
Bleeder Hole Center To Threaded End Distance:	0.406 Inches Minimum And 0.438 Inches Maximum
Bleeder Hole Diameter:	0.062 Inches Nominal
Thread Quantity Per Inch:	12 External
Nominal Thread Size:	1.312 Inches External
Seat Angle:	45.0 Degrees
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall
Style Designator:	Plug, Machine W/bleeder Holes
Thread Series Designator:	Un External

How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169D16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.