

Description

Thread Size: 1-5/8", Length: 1-1/8", Thread Length: 1/2",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS5169D20L
Minimum Qty (MOQ):	1
NSN:	5365-01-122-8570
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE
AVAILABLE

P/N AS5169D20L Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Thread Length:	0.500 Inches Minimum External And 0.515 Inches Maximum External
Head Height:	0.438 Inches Nominal
Overall Length:	1.094 Inches Nominal
Unable To Decode:	Unable To Decode
Connection Style:	Plain
Body Core Diameter:	1.078 Inches Nominal
Core Depth:	0.593 Inches Minimum And 0.609 Inches Maximum
Bleeder Hole Center To Threaded End Distance:	0.313 Inches Minimum And 0.375 Inches Maximum
Bleeder Hole Diameter:	0.062 Inches Nominal
Head Core Diameter:	1.625 Inches Nominal
Head Type:	Cored
Body Type:	Cored
Thread Quantity Per Inch:	12 External
Nominal Thread Size:	1.625 Inches External
Special Features:	Core Depth Of Head 0.125 In.,width Across Flats 1.869 In. Min 1.881 In. Max
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/4 T6 Fed Spec 1st Material Response Overall Or Qq-a-225/6 T6 Fed Spec 2nd Material Response Overall Or Qq-a-225/9 T73 Fed Spec 3rd Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Type 2 Class 2 Mil Spec Single Treatment Response Overall
Style Designator:	Plug, Machine W/bleeder Holes
Thread Series Designator:	Un External

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/AS5169D20L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.