

**Description**

Thread Size: 1/4", Length: 5/8", Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                       |
|-------------------------|-----------------------|
| SKU / Model:            | AS5169K02L            |
| Minimum Qty (MOQ):      | 1                     |
| NSN:                    | 5365-01-206-8068      |
| ECCN:                   | EAR99                 |
| National Motor Freight: | 095190, Hardware, Noi |



## P/N AS5169K02L Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a External   |
| <b>Thread Direction:</b>                              | Right-hand External                                     |
| <b>Thread Length:</b>                                 | 0.251 Inches Nominal External                           |
| <b>Head Height:</b>                                   | 0.250 Inches Nominal                                    |
| <b>Overall Length:</b>                                | 0.594 Inches Nominal                                    |
| <b>Unable To Decode:</b>                              | Unable To Decode  |
| <b>Connection Style:</b>                              | Plain   |
| <b>Body Core Diameter:</b>                            | 0.062 Inches Nominal                                    |
| <b>Core Depth:</b>                                    | 0.250 Inches Minimum And 0.266 Inches Maximum           |
| <b>Bleeder Hole Center To Threaded End Distance:</b>  | 0.125 Inches Minimum And 0.187 Inches Maximum           |
| <b>Bleeder Hole Diameter:</b>                         | 0.062 Inches Nominal                                    |
| <b>Head Core Diameter:</b>                            | 0.312 Inches Nominal                                    |
| <b>Head Type:</b>                                     | Cored   |
| <b>Body Type:</b>                                     | Cored   |
| <b>Nominal Thread Size:</b>                           | 0.312 Inches External                                   |
| <b>Special Features:</b>                              | Hex Head,width Across Flats 0.559 In. Min,0.567 In. Max |
| <b>Material:</b>                                      | Steel Comp 316 Overall                                  |
| <b>Material Document And Classification:</b>          | Qq-s-763 Fed Spec Single Material Response Overall      |
| <b>Surface Treatment:</b>                             | Passivate Overall                                       |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall      |
| <b>Style Designator:</b>                              | Plug, Machine W/bleeder Holes                           |
| <b>Thread Series Designator:</b>                      | Unf External  |

## How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/AS5169K02L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.