

Description

Thread Size: 1/4", Length: 5/8", Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS5169K02L
Minimum Qty (MOQ):	1
NSN:	5365-01-206-8068
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



P/N AS5169K02L Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Thread Length:	0.251 Inches Nominal External
Head Height:	0.250 Inches Nominal
Overall Length:	0.594 Inches Nominal
Unable To Decode:	Unable To Decode
Connection Style:	Plain
Body Core Diameter:	0.062 Inches Nominal
Core Depth:	0.250 Inches Minimum And 0.266 Inches Maximum
Bleeder Hole Center To Threaded End Distance:	0.125 Inches Minimum And 0.187 Inches Maximum
Bleeder Hole Diameter:	0.062 Inches Nominal
Head Core Diameter:	0.312 Inches Nominal
Head Type:	Cored
Body Type:	Cored
Nominal Thread Size:	0.312 Inches External
Special Features:	Hex Head,width Across Flats 0.559 In. Min,0.567 In. Max
Material:	Steel Comp 316 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Plug, Machine W/bleeder Holes
Thread Series Designator:	Unf External

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/AS5169K02L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.