

Description

aluminum - male to male external thread - 37°, flared tube - large end - tube outer dia: 5/8", thread: 7/8-14 "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------|
| SKU / Model: | AS5174D1008 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-187-3588 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



* See page 2 for technical characteristics

P/N AS5174D1008 Specifications

| | |
|--|--|
| Thread Class: | 3a All Ends |
| Reducer Type: | Concentric |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit Single Response |
| End Item Identification: | Aircraft Fluid Systems |
| Connection Style: | Flared W/ Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.750 Inches 2nd End |
| Nominal Thread Size: | 0.875 Inches 1st End |
| Nominal Overall Length: | 1.750 Inches |
| Material: | Aluminum Alloy 2014 Overall |
| Material Document And Classification: | Qq-a-225/4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Thread Series Designator: | Unf 2nd End |
| Thread Series Designator: | Unjf 1st End |
| Specification/standard Data: | 88044-an919 Government Standard |

How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AS5174D1008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.