

P/N AS5174D1210

Description

aluminum, male to male external thread, flared tube, large end, tube outer diameter: 3/4", thread: 1-1/16-12

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

AN919-20D

SKU / Model: AS5174D1210

Minimum Qty (MOQ):

NSN: 4730-00-805-5100

ECCN: EAR99

National Motor Freight: 051400, Pipe Fittings Aluminum









P/N AS5174D1210 Specifications

Thread Class:	3a All Ends
Reducer Type:	Concentric
Maximum Operating Temp:	225.0 Deg Fahrenheit Single Response
Connection Style:	Flared (tube) All Ends
Connection Type:	Threaded External Tube All Ends
Thread Quantity Per Inch:	12 1st End
Nominal Thread Size:	0.875 Inches 2nd End
Nominal Thread Size:	1.062 Inches 1st End
Seat Angle:	37.0 Degrees All Ends
Criticality Code Justification:	Feat
Nominal Outside Diameter Tube Accommodated:	0.625 Inches 2nd End
Nominal Outside Diameter Tube Accommodated:	0.750 Inches 1st End
Nominal Overall Length:	2.000 Inches
Special Features:	Supports Grumman A10a Aircraft;weapon System Essential
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec 1st Material Response Overall Or Qq-a-225/6,t6 Fed Spec 2nd Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unj 1st End
Thread Series Designator:	Unjf 2nd End
Specification/standard Data:	96906-ms24399 Government Standard And 81349-mil-f-5509 Government Specification

How to Order

Order this tube reducer from our inventory online by visiting https://military-fasteners.com/fittings/tube+reducers/AS5174D1210 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.