

**Description**

male to male union, external thread, flared tube, large end, tube outer diameter: 5/8", thread: 7/8-14, corrosion resistant steel, new revision, AS5174 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AN919-15J](#)

SKU / Model:	AS5174J1008
Minimum Qty (MOQ):	1
NSN:	4730-01-533-1475
Schedule B:	7307.22.1000
ECCN:	EAR99



\* See page 2 for technical characteristics

# P/N AS5174J1008 Specifications

<b>Thread Class:</b>	3a All Ends
<b>End Item Identification:</b>	Rq-4a
<b>Connection Style:</b>	Flared W/ Gasket Seal (boss) All Ends
<b>Nominal Width:</b>	1.128 Inches 1st End
<b>Nominal Length:</b>	1.750 Inches All Ends
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.750 Inches 2nd End
<b>Nominal Thread Size:</b>	0.875 Inches 1st End
<b>Part Name Assigned By Controlling Agency:</b>	Fitting, Union And Reducer, Flared
<b>Material:</b>	Steel Comp 304 Overall
<b>Material Document And Classification:</b>	Ms5639 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf All Ends

## How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AS5174J1008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.