

Description

male to male union, external thread, flared tube, large end, tube outer diameter: 5/8", thread: 7/8-14, corrosion resistant steel, new revision, AS5174 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN919-15J](#)

SKU / Model:	AS5174J1008
Minimum Qty (MOQ):	1
NSN:	4730-01-533-1475
Schedule B:	7307.22.1000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N AS5174J1008 Specifications

Thread Class:	3a All Ends
End Item Identification:	Rq-4a
Connection Style:	Flared W/ Gasket Seal (boss) All Ends
Nominal Width:	1.128 Inches 1st End
Nominal Length:	1.750 Inches All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.750 Inches 2nd End
Nominal Thread Size:	0.875 Inches 1st End
Part Name Assigned By Controlling Agency:	Fitting, Union And Reducer, Flared
Material:	Steel Comp 304 Overall
Material Document And Classification:	Ms5639 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf All Ends

How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AS5174J1008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.