

Description

tube outer dia: 3/4", flared tube fitting - corrosion resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS5176J12
Minimum Qty (MOQ):	2
NSN:	4730-00-204-3454
Schedule B:	7307.22.1000
ECCN:	9A991
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N AS5176J12 Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.688 Inches Nominal
Flange Width:	0.266 Inches Nominal
Flange Outside Diameter:	0.972 Inches Nominal
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	0.826 Inches Nominal
Hose/tube Outside Diameter For Which Designed:	0.750 Inches Nominal
Material:	Steel, Qq-s-763, Class 304
Material:	Steel Comp 304
Surface Treatment:	Passivated,qq-p-35,type 1
Style Designator:	Sleeve
Surface Treatment:	Passivated,qq-p-35,type 1

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/AS5176J12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.