

**Description**

tube outer diameter: 3/8", thread: 9/16-18, aluminum"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AS5179D06
Minimum Qty (MOQ):	5
NSN:	4730-00-277-5083
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

## P/N AS5179D06 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Fabrication Method:</b>	Machined
<b>Nut Style:</b>	Tube Fitting Locknut
<b>Nut Height:</b>	0.250 Inches Minimum And 0.282 Inches Maximum
<b>Width Across Flats:</b>	0.809 Inches Minimum And 0.816 Inches Maximum
<b>Thread Series:</b>	Unjf
<b>Packing Recess Diameter:</b>	0.728 Inches Minimum And 0.738 Inches Maximum
<b>Packing Recess Depth:</b>	0.037 Inches Minimum And 0.047 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Nominal Thread Size:</b>	0.562 Inches
<b>Nominal Tube Outside Diameter:</b>	0.375 Inches
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Qq-a-225/6 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	88044-an6289 Government Standard

## How to Order

Order this tube fitting locknut from our inventory online by visiting <https://military-fasteners.com/fittings/tube+fitting+locknuts/AS5179D06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.