

**Description**

aluminum cap for flared fittings, tube size: 5/8", thread: 7/8-14

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                    |
|-------------------------|------------------------------------|
| SKU / Model:            | ASC10                              |
| Minimum Qty (MOQ):      | 25                                 |
| NSN:                    | 5340-01-132-3808                   |
| ECCN:                   | EAR99                              |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



\* See page 2 for technical characteristics

## P/N ASC-10 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 2b   |
| <b>Design Type:</b>                                   | Threaded   |
| <b>Inside Diameter Length:</b>                        | 0.630 Inches Nominal   |
| <b>Round Cap Outside Surface Condition:</b>           | Smooth Or Serrated   |
| <b>Special Features:</b>                              | Color Yellow   |
| <b>Material:</b>                                      | Aluminum Alloy 3003  |
| <b>Material Document And Classification:</b>          | Alloy 3003-0 Assn Std Single Material Response                 |
| <b>Surface Treatment:</b>                             | Anodize  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625, Type 2, Class 2 Mil Spec Single Treatment Response |
| <b>Thread Size And Series/type Designator:</b>        | 0.875-14 Unf   |

## How to Order

Order this protective dust and moisture cap from our inventory online by visiting <https://military-fasteners.com/caplugs/protective+dust+and+moisture+caps/ASC-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.