

P/N B100-EU05-05

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: B100EU0505

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-124-0550

Schedule B: 7318.23.0000

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N B100-EU05-05 Specifications

| Fastener Length: | 0.467 Inches Maximum |
|--|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.334 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.281 Inches Minimum And 0.345 Inches Maximum |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/B100-EU05-05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/B100-EU05-05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/B100-EU05-05 and selecting the quantity you want then click "add to cart".