

## P/N B1821AH025C063N

## **Description**

Fastener Length: 5/8", Thread: 1/4-20, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: B1821AH025C063N

Minimum Qty (MOQ): 145 EA

NSN: 5305-01-457-8854

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N B1821AH025C063N Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.470 Inches Minimum And 0.582 Inches Maximum
Fastener Length:	0.595 Inches Minimum And 0.625 Inches Maximum
Head Style:	Hexagon
Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.438 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall And 39.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Astm A354 Gr Bd Gr 8 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821AH025C063N">https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821AH025C063N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.