

P/N B1821BH025C075L

Description

Fastener Length: 3/4", Thread: 1/4-20, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: B1821BH025C075L

Minimum Qty (MOQ): 25 EA

NSN: 5306-01-175-7558

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N B1821BH025C075L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.438 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Nominal Thread Diameter:	0.250 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Fastener And 38.0 Rockwell C Maximum Fastener
Material:	Plastic Polyamide Locking Feature
Material:	Steel Fastener
Material Document And Classification:	Sae J429,grade 8 Assn Std Single Material Response Fastener Or Astm A354,grade Bd Assn Std Single Material Response Fastener
Surface Treatment:	Zinc Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821BH025C075L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://energia.com/screws/hexagon+head+cap+screws/B1821BH025C075L and selecting the