

## P/N B1821BH025C138L

## **Description**

Fastener Length: 1-3/8", Thread: 1/4-20, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: B1821BH025C138L

Minimum Qty (MOQ): 20 EA

NSN: 5306-01-203-6433

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N B1821BH025C138L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum
Fastener Length:	1.313 Inches Minimum And 1.375 Inches Maximum
Head Style:	Hexagon
Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Width Between Flats:	0.4280 Inches Minimum And 0.4375 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Nominal Thread Diameter:	0.250 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	2.0 Rockwell C Minimum Fastener And 38.0 Rockwell C Maximum Fastener
Special Features:	Locking Feature Material Epoxy Plastic
Material:	Plastic Polyamide Locking Feature
Material:	Steel Fastener
Material:	Steel Overall
Material Document And Classification:	Sae J429,grade 8 Assn Std Single Material Response Fastener Or Astm A354,grade Bd Assn Std Single Material Response Fastener
Surface Treatment:	Zinc Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Fastener
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/B1821BH025C138L">https://military-fasteners.com/screws/machine+screws/B1821BH025C138L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.