

**Description**

Fastener Length: 1-63/64", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	B1821BH031F200D
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-273-1489
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N B1821BH031F200D Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.864 Inches Minimum And 1.052 Inches Maximum
<b>Fastener Length:</b>	1.938 Inches Minimum And 2.000 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.195 Inches Minimum And 0.211 Inches Maximum
<b>Width Between Flats:</b>	0.489 Inches Minimum And 0.500 Inches Maximum
<b>Hole Diameter:</b>	0.060 Inches Minimum And 0.068 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	150000 Pounds Per Square Inch
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Sae Grade 8 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Zinc Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Astm B633 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	2 Type And 10p Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/B1821BH031F200D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.