

Description

Fastener Length: 1-63/64", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | B1821BH031F200D |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5305-01-273-1489 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N B1821BH031F200D Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.864 Inches Minimum And 1.052 Inches Maximum |
| Fastener Length: | 1.938 Inches Minimum And 2.000 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.195 Inches Minimum And 0.211 Inches Maximum |
| Width Between Flats: | 0.489 Inches Minimum And 0.500 Inches Maximum |
| Hole Diameter: | 0.060 Inches Minimum And 0.068 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Flats |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Grade 8 Assn Std Single Material Response Overall |
| Surface Treatment: | Zinc Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Astm B633 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 2 Type And 10p Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/B1821BH031F200D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.