

Description

Fastener Length: 7/16", Thread: 3/8-16, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	B1821BH038C044L
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-229-9592
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N B1821BH038C044L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Hexagon
Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
Width Between Flats:	0.551 Inches Minimum And 0.562 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Nominal Thread Diameter:	0.375 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Fastener And 39.0 Rockwell C Maximum Fastener
Material:	Plastic Polyamide Locking Feature
Material:	Steel Fastener
Material:	Steel Overall
Material Document And Classification:	Sae J429,grade 8 Assn Std Single Material Response Fastener Or Astm A354,grade Bd Assn Std Single Material Response Fastener
Surface Treatment:	Zinc Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821BH038C044L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.