



Military-Fasteners.com

P/N B1821BH038C044L

Description

Fastener Length: 7/16", Thread: 3/8-16, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	B1821BH038C044L
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-229-9592
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N B1821BH038C044L Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.251 Inches Minimum And 0.438 Inches Maximum
<b>Fastener Length:</b>	0.407 Inches Minimum And 0.438 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.226 Inches Minimum And 0.243 Inches Maximum
<b>Width Between Flats:</b>	0.551 Inches Minimum And 0.562 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Strip Threads
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	150000 Pounds Per Square Inch
<b>Hardness Rating:</b>	33.0 Rockwell C Minimum Fastener And 39.0 Rockwell C Maximum Fastener
<b>Material:</b>	Plastic Polyamide Locking Feature
<b>Material:</b>	Steel Fastener
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Sae J429,grade 8 Assn Std Single Material Response Fastener Or Astm A354,grade Bd Assn Std Single Material Response Fastener
<b>Surface Treatment:</b>	Zinc Fastener And Chromate Fastener
<b>Surface Treatment Document And Classification:</b>	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821BH038C044L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.