

P/N B1821BH038C125L

Description

Fastener Length: 1-1/4", Thread: 3/8-16, Thread Length: 1-3/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: B1821BH038C125L

Minimum Qty (MOQ): 30 EA

NSN: 5306-01-112-8681

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N B1821BH038C125L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Minimum And 1.188 Inches Maximum
Fastener Length:	1.125 Inches Minimum And 1.250 Inches Maximum
Head Style:	Hexagon
Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
Width Between Flats:	0.551 Inches Minimum And 0.562 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Nominal Thread Diameter:	0.375 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Fastener And 38.0 Rockwell C Maximum Fastener
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Plastic Polyamide Locking Feature
Material:	Steel Fastener
Material Document And Classification:	Sae J429,grade 8 Assn Std Single Material Response Fastener Or Astm A354,grade Bd Assn Std Single Material Response Fastener
Surface Treatment:	Zinc Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821BH038C125L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.