

P/N B1821BH038F125L

Military-Fasteners.com

## Description

self-locking, B1821BH series bolt

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS90727-62L	
SKU / Model:	B1821BH038F125L
Minimum Qty (MOQ):	25
NSN:	5305-01-140-6356
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N B1821BH038F125L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Unable To Decode:	Unable To Decode And Unable To Decode
Fastener Length:	1.188 Inches Minimum And 1.250 Inches Maximum
Unable To Decode:	Unable To Decode
Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
Width Between Flats:	0.551 Inches Minimum And 0.562 Inches Maximum
Locking Feature:	Patch Or Strip
Nominal Thread Diameter:	0.375 Inches
Unable To Decode:	Unable To Decode
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Material:	Plastic Polyamide
Material:	Steel
Material Document And Classification:	Sae J429 Grade 8 Assn Std Single Material Response
Unable To Decode:	Unable To Decode And Unable To Decode
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response
Thread Series Designator:	Unf
Unable To Decode:	Unable To Decode And Unable To Decode And Unable To Decode

## How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/B1821BH038F125L</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.