

## P/N B1821BH038F175N

## **Description**

thread: 3/8-24, length: 1-3/4",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS90726-65

SKU / Model: B1821BH038F175N

Minimum Qty (MOQ): 50

NSN: 5305-00-269-3241

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N B1821BH038F175N Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Minimum And 1.188 Inches Maximum
Fastener Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
Width Between Flats:	0.551 Inches Minimum And 0.562 Inches Maximum
End Item Identification:	Mrap-rg-33 Armored Utility Vehicle (auv)
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae Gr 8 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this hexagon head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821BH038F175N">https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821BH038F175N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.