

Description

Fastener Length: 3/4", Thread: 1/2-13, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | B1821BH050C075N |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5305-00-732-0512 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N B1821BH050C075N Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.527 Inches Minimum And 0.750 Inches Maximum |
| Fastener Length: | 0.719 Inches Minimum And 0.750 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.302 Inches Minimum And 0.323 Inches Maximum |
| Width Between Flats: | 0.736 Inches Minimum And 0.750 Inches Maximum |
| End Item Identification: | Nsn 4210-01-486-1035 Tfft (tactical Fire Fighting Truck) |
| Nominal Thread Diameter: | 0.500 Inches |
| Thread Quantity Per Inch: | 13 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Surface Finish: | 63.0 Microinches Threads |
| Material: | Steel Overall |
| Material Document And Classification: | Saej429 Grade 8 Assn Std 1st Material Response Overall Or Astma354 Grade Bd Assn Std 2nd Material Response Overall |
| Surface Treatment: | Zinc Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821BH050C075N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.