

Description

Fastener Length: 1-63/64", Hole Diameter: 3/32", Thread: 5/8-18, Thread Length: 1-23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	B1821BH063F200D
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-943-7015
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N B1821BH063F200D Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.500 Inches Minimum And 1.719 Inches Maximum
Fastener Length:	1.920 Inches Minimum And 2.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.378 Inches Minimum And 0.403 Inches Maximum
Width Between Flats:	0.922 Inches Minimum And 0.937 Inches Maximum
Hole Diameter:	0.094 Inches Nominal
Nominal Thread Diameter:	0.625 Inches
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Minimum Yield Strength:	120000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Steel Overall
Material Document And Classification:	Sae Gr 8 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/B1821BH063F200D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.