

Description

Fastener Length: 1-63/64", Hole Diameter: 3/32", Thread: 5/8-18, Thread Length: 1-23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | B1821BH063F200D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-943-7015 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N B1821BH063F200D Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.500 Inches Minimum And 1.719 Inches Maximum |
| Fastener Length: | 1.920 Inches Minimum And 2.000 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.378 Inches Minimum And 0.403 Inches Maximum |
| Width Between Flats: | 0.922 Inches Minimum And 0.937 Inches Maximum |
| Hole Diameter: | 0.094 Inches Nominal |
| Nominal Thread Diameter: | 0.625 Inches |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 120000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Flats |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Gr 8 Assn Std Single Material Response Overall |
| Surface Treatment: | Zinc Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/B1821BH063F200D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.