

P/N B1821BH063F325N

Description

Fastener Length: 3-1/4", Thread: 5/8-18, Thread Length: 1-11/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: B1821BH063F325N

Minimum Qty (MOQ): 15 EA

NSN: 5305-00-726-2556

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N B1821BH063F325N Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.500 Inches Minimum And 1.688 Inches Maximum
Fastener Length:	3.250 Inches Nominal
Head Style:	Hexagon
Head Height:	0.378 Inches Minimum And 0.403 Inches Maximum
Width Between Flats:	0.922 Inches Minimum And 0.938 Inches Maximum
lii End Item Identification:	Mrap Buffalo Mk2a2
Nominal Thread Diameter:	0.625 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Hardness Rating:	32.0 Rockwell C Minimum And 38.0 Rockwell C Maximum Overall
Minimum Yield Strength:	120000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Sae Gr 8 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment:	Zinc And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/hexagon+head+cap+screws/B1821BH063F325N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.