

Description

Fastener Length: 4-1/2", Thread: 7/8-14, Thread Length: 2-3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	B1821BH088F450N
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-926-5517
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N B1821BH088F450N Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	2.000 Inches Minimum And 2.188 Inches Maximum
Fastener Length:	4.500 Inches Nominal
Head Style:	Hexagon
Head Height:	0.531 Inches Minimum And 0.563 Inches Maximum
Width Between Flats:	1.285 Inches Minimum And 1.312 Inches Maximum
End Item Identification:	Mrap Rg-33
Nominal Thread Diameter:	0.875 Inches
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae J429 Gr 8 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	2 Type And 10p Style And 8 Grade

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/B1821BH088F450N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.