

Description

Fastener Length: 55/64", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACB30BF3C7 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-142-4415 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N BACB30BF3C7 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.381 Inches Minimum And 0.431 Inches Maximum |
| Fastener Length: | 0.829 Inches Minimum And 0.859 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.332 Inches Minimum And 0.387 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams5732 Assn Std Single Material Response |
| Shank Surface Finish: | 63.0 Microinches |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30BF3C7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.