

Description

Length: 17/32", Thread: 10-32, Thread Length: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | BACB30BF3K2 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-639-4311 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |



P/N BACB30BF3K2 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.406 Inches Minimum |
| Fastener Length: | 0.516 Inches Minimum And 0.546 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.332 Inches Minimum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Nickel Alloy K-500 Or Copper Alloy 172 |
| Screw Material Document And Classification: | Qq-n-286 Cl A Fed Spec 1st Material Response Or Qq-c-530 Cond A Fed Spec 2nd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30BF3K2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.