

**Description**

Fastener Length: 1-3/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | BACB30BH3C11                              |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-957-3718                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N BACB30BH3C11 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.319 Inches Minimum And 0.369 Inches Maximum                       |
| <b>Fastener Length:</b>   | 1.017 Inches Minimum And 1.047 Inches Maximum                       |
| <b>Head Style:</b>  | Hexagon   |
| <b>Head Height:</b>   | 0.078 Inches Minimum And 0.110 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.365 Inches Minimum And 0.377 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.1889 Inches Minimum And 0.1894 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.070 Inches Minimum First Hole And 0.075 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.190 Inches  |
| <b>Grip Length:</b>   | 0.678 Inches Minimum And 0.698 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>  | 32  |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.860 Inches Minimum First Hole And 0.892 Inches Maximum First Hole |
| <b>Surface Finish:</b>  | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>  | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>  | 32.0 Microinches Threads  |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>                            | Ams 5732 Assn Std Single Material Response Overall                  |
| <b>Thread Series Designator:</b>  | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30BH3C11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.