

Description

Fastener Length: 1-3/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30BH3C11
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-957-3718
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACB30BH3C11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.319 Inches Minimum And 0.369 Inches Maximum
Fastener Length:	1.017 Inches Minimum And 1.047 Inches Maximum
Head Style:	Hexagon
Head Height:	0.078 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Grip Diameter:	0.1889 Inches Minimum And 0.1894 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.075 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.860 Inches Minimum First Hole And 0.892 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30BH3C11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.