

P/N BACB30BH4C15

Description

Fastener Length: 1-21/64", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

 SKU / Model:
 BACB30BH4C15

 Minimum Qty (MOQ):
 5 EA

 NSN:
 5306-00-960-5455

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30BH4C15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
	0.389 Inches Nominal
Thread Length:	
Fastener Length:	1.312 Inches Minimum And 1.342 Inches Maximum
Head Style:	Undercut Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2496 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hole Configuration Style:	Hexagon Corners
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.186 Inches Minimum First Hole And 1.236 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30BH4C15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.