

P/N BACB30BH4C20

Description

Fastener Length: 1-19/32", Thread: 1/4-20, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30BH4C20

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-889-3094

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30BH4C20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Minimum
Fastener Length:	1.594 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Grip Diameter:	0.2487 Inches Minimum And 0.2492 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.250 Inches Nominal
Thread Quantity Per Inch:	20
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.438 Inches Nominal First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	81205-bacb30bh Manufacturers Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30BH4C20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30BH4C20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30BH4C20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30BH4C20 and selecting the quantity you want then click "add to cart".