



Military-Fasteners.com

P/N BACB30BH6-12

Description

Fastener Length: 1-7/64", Thread: 3/8-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACB30BH612 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-185-8677 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N BACB30BH6-12 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.334 Inches Minimum And 0.384 Inches Maximum |
| Fastener Length: | 1.094 Inches Minimum And 1.124 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.172 Inches Minimum And 0.204 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.565 Inches Maximum |
| Grip Diameter: | 0.3737 Inches Minimum And 0.3742 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.111 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.953 Inches Minimum First Hole And 0.985 Inches Maximum First Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30BH6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.