

Description

Fastener Length: 63/64", Thread: 3/8-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30BH6C10A
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-933-4968
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACB30BH6C10A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.334 Inches Minimum And 0.384 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 0.999 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Grip Diameter:	0.3737 Inches Minimum And 0.3742 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30BH6C10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.