

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30EL3C3
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-517-3067
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N BACB30EL3C3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Nominal
Fastener Length:	0.463 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.258 Inches Minimum And 0.305 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.187 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Nas 498 Assn Std Single Material Response Overall Or Mil-s-6758 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-a-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30EL3C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.