



Military-Fasteners.com

P/N BACB30FD5H5P

Description

Fastener Length: 1-17/64", Hole Diameter: 3/64", Thread: 1/4-24, Thread Length: 29/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30FD5H5P
Minimum Qty (MOQ):	2
NSN:	5306-01-531-5231
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30FD5H5P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.882 Inches Minimum And 0.912 Inches Maximum
Fastener Length:	1.220 Inches Minimum And 1.270 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.338 Inches Minimum And 0.358 Inches Maximum
Hole Diameter:	0.050 Inches Minimum And 0.060 Inches Maximum
Single Shear Strength:	102000 Pounds Per Square Inch
End Item Identification:	1520-01-088-3669
Nominal Thread Diameter:	0.312 Inches
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	0.0 Microinches Overall
Part Name Assigned By Controlling Agency:	External Wrenching, 180 Ksi Mintensile, 102 Ksi Min Shear, 4340 Or 8740 Steel; 450 F
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec All Material Responses Overall Or Mil-s-6049 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas672 Assn Std All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30FD5H5P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.