

Description

Fastener Length: 1-1/2", Hole Diameter: ", Thread: 3/8-24, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30FD6H14
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-025-4820
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30FD6H14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum And 0.644 Inches Maximum
Fastener Length:	1.479 Inches Minimum And 1.509 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.378 Inches Minimum And 0.398 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.081 Inches Minimum And 0.101 Inches Maximum
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Assn Std 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30FD6H14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.