

**Description**

Fastener Length: 1-1/2", Thread Size: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30FM16A14U
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-467-2218
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

# P/N BACB30FM16A14U Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.560 Inches Nominal
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.103 Inches Minimum And 0.115 Inches Maximum
<b>Width Between Flats:</b>	0.220 Inches Minimum And 0.224 Inches Maximum
<b>Shank Diameter:</b>	0.4990 Inches Nominal
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.735 Inches Minimum And 0.770 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>End Item Identification:</b>	Aircraft, Awacs, E-3a; Aircraft, Stratolifter C-135,group B
<b>Grip Length:</b>	0.875 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Nominal Thread Size:</b>	0.500 Inches
<b>Special Features:</b>	End Shall Be Flat And Chamfered;not Available In Diameters Larger Than .500in;unjf-3a (except Unjc-3a For .1640-32)thread Per Mil-s-8879, Rolled, Except Major Diameter Shall Conform To "td";inspection Report Shall Provide Name Of Coating Applicater In Addition To Procuremnt Specification Requirements;maximum "d" Diameter May Be Exceeded By >0002 Inches For Dry Film Lube Bolts;identify With Green Dye Or Paint On Thread End Before Lubrication; Coverage Of Dye Or Paint May Include Chamfer Dimention Plus One Pitch;cetyl Alcohol Lube;end Item E-3a
<b>Material:</b>	Steel Comp 8740 Overall Or Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams-s-6758 Assn Std Single Material Response Overall Or Ams-s-6382 Assn Std Single Material Response Overall Or Ams-s-6349 Assn Std Single Material Response Overall Or Ams6415 Assn Std Single Material Response Overall Or Ams6484 Assn Std Single Material Response Overall Or Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type2,class2 Fed Spec Single Treatment Response Overall And Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30FM16A14U> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.