

**Description**

Fastener Length: 1/2", Thread Size: 5/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | BACB30FM53                  |
| Minimum Qty (MOQ):      | 20 EA                       |
| NSN:                    | 5320-00-959-0334            |
| Schedule B:             | 7318.24.0000                |
| ECCN:                   | EAR99                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N BACB30FM5-3 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Identification Code Color:</b>                     | Bronze   |
| <b>Fastener Length:</b>                               | 0.490 Inches Minimum And 0.510 Inches Maximum                                  |
| <b>Head Height:</b>                                   | 0.037 Inches Minimum And 0.047 Inches Maximum                                  |
| <b>Width Between Flats:</b>                           | 0.0791 Inches Minimum And 0.0801 Inches Maximum                                |
| <b>Shank Diameter:</b>                                | 0.1625 Inches Minimum And 0.1635 Inches Maximum                                |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded  |
| <b>Head Major Diameter:</b>                           | 0.242 Inches Minimum And 0.262 Inches Maximum                                  |
| <b>Lubrication:</b>                                   | Cetyl Alcohol, Spec 305, Hi-shear Corp   |
| <b>Grip Length:</b>                                   | 0.193 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Nominal Thread Size:</b>                           | 0.164 Inches   |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch  |
| <b>Special Features:</b>                              | Color Bronze   |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall               |
| <b>Thread Series Designator:</b>                      | Unjc   |

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/BACB30FM5-3](https://military-fasteners.com/rivets/pin_rivets/BACB30FM5-3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.