

Description

Fastener Length: 1-21/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | BACB30FM815 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-209-4139 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N BACB30FM8-15 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 1.323 Inches Minimum And 1.343 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.059 Inches Minimum And 0.069 Inches Maximum |
| Width Between Flats: | 0.096 Inches Nominal |
| Shank Diameter: | 0.248 Inches Nominal |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.387 Inches Minimum And 0.412 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.933 Inches Minimum And 0.943 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Material: | Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4340 Overall |
| Material Document And Classification: | Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/BACB30FM8-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.