

Description

Fastener Length: 1-49/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30FM822
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-524-6005
Schedule B:	7318.24.0000
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N BACB30FM8-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.770 Inches Nominal
Head Style:	Err-090
Head Height:	0.056 Inches Minimum And 0.069 Inches Maximum
Width Between Flats:	0.094 Inches Minimum And 0.096 Inches Maximum
Shank Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	1.375 Inches Nominal
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Ams 6415 Assn Std 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/BACB30FM8-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.