

P/N BACB30FN5-12

Description

Thread Size: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30FN512

Minimum Qty (MOQ): 10 EA

NSN: 5320-01-045-2522

Schedule B: 7318.24.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N BACB30FN5-12 Specifications

Thread Class: 3a Thread Direction: Right-hand Fastener Length: 1.052 Inches Minimum And 1.072 Inches Maximum Head Style: Flush Countersunk Width Between Flats: 0.0791 Inches Minimum And 0.0801 Inches Maximum Shank Diameter: 0.1625 Inches Minimum And 0.1635 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.2612 Inches Maximum Grip Length: 0.755 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.164 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication,color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Poursel Overall Or Mil-s-5000 Poursel Overall Or Mil-s-5000 Poursel Overall Or Mil-s-5000 Poursel Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 2nd Mate		
Fastener Length:	Thread Class:	3a
Head Style: Flush Countersunk Width Between Flats: 0.0791 Inches Minimum And 0.0801 Inches Maximum Shank Diameter: 0.1625 Inches Minimum And 0.1635 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.2612 Inches Maximum Grip Length: 0.755 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.164 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication, color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Thread Direction:	Right-hand
Width Between Flats:0.0791 Inches Minimum And 0.0801 Inches MaximumShank Diameter:0.1625 Inches Minimum And 0.1635 Inches MaximumShank Style:Pin-rivet, Straight, ThreadedHead Major Diameter:0.2612 Inches MaximumGrip Length:0.755 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchNominal Thread Size:0.164 InchesShear Strength:95000 Single Pounds Per Square InchCountersink Angle:100.0 Degrees NominalSpecial Features:Cetyl Alcohol Lubrication, color BronzeMaterial:Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rdSurface Treatment:Cadmium Overall	Fastener Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Shank Diameter: Din-rivet, Straight, Threaded Head Major Diameter: O.2612 Inches Maximum O.755 Inches Maximum Grip Length: O.755 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: O.164 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication, color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Head Style:	Flush Countersunk
Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.2612 Inches Maximum Grip Length: 0.755 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.164 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication,color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Width Between Flats:	0.0791 Inches Minimum And 0.0801 Inches Maximum
Head Major Diameter: 0.2612 Inches Maximum Grip Length: 0.755 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.164 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication,color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Grip Length: 0.755 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.164 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication,color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Shank Style:	Pin-rivet, Straight, Threaded
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.164 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication, color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Head Major Diameter:	0.2612 Inches Maximum
Minimum Tensile Strength: Nominal Thread Size: 0.164 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication,color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Cadmium Overall	Grip Length:	0.755 Inches Maximum
Nominal Thread Size: 5hear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication,color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Thread Quantity Per Inch:	32
Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Special Features: Cetyl Alcohol Lubrication,color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle: Special Features: Cetyl Alcohol Lubrication, color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Cadmium Overall	Nominal Thread Size:	0.164 Inches
Special Features: Cetyl Alcohol Lubrication,color Bronze Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Shear Strength:	95000 Single Pounds Per Square Inch
Material:Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 OverallMaterial Document AndMil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rdClassification:Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response OverallSurface Treatment:Cadmium Overall	Countersink Angle:	100.0 Degrees Nominal
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Special Features:	Cetyl Alcohol Lubrication, color Bronze
Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall	Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And	Surface Treatment:	Cadmium Overall
Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjc	Thread Series Designator:	Unjc

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/BACB30FN5-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/pin_rivets/BACB30FN5-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/pin_rivets/BACB30FN5-12 and selecting the quantity you want then click "add to cart".