

Description

BACB30FP10-7 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | BACB30FP107 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-178-6248 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

P/N BACB30FP10-7 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.928 Inches Minimum And 0.948 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.068 Inches Minimum And 0.078 Inches Maximum |
| Width Between Flats: | 0.1270 Inches Minimum And 0.1295 Inches Maximum |
| Shank Diameter: | 0.3266 Inches Minimum And 0.3276 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.475 Inches Minimum And 0.505 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.443 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Nominal Thread Size: | 0.312 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/BACB30FP10-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.