

P/N BACB30FP6-3

Description

Fastener Length: 33/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30FP63

Minimum Qty (MOQ): 20 EA

NSN: 5320-01-043-0071

Schedule B: 7318.24.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N BACB30FP6-3 Specifications

| Right-hand Fastener Length: 0.503 Inches Minimum And 0.523 Inches Maximum Head Style: Err-090 Head Height: 0.045 Inches Minimum And 0.055 Inches Maximum Width Between Flats: 0.0791 Inches Minimum And 0.0806 Inches Maximum Width Between Flats: 0.0791 Inches Minimum And 0.02026 Inches Maximum Shank Diameter: 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | | |
|--|---------------------------|---|
| Asstener Length: 0.503 Inches Minimum And 0.523 Inches Maximum Head Style: Err-090 Head Height: 0.045 Inches Minimum And 0.0856 Inches Maximum Width Between Flats: 0.0791 Inches Minimum And 0.0806 Inches Maximum Shank Diameter: 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Oq-p-416.ty 2.cl 2 Fed Spec Single Treatment Response Overall Oq-p-416.ty 2.cl 2 Fed Spec Single Treatment Response Overall | Thread Class: | 3a |
| Head Style: Head Height: O.045 Inches Minimum And O.055 Inches Maximum Width Between Flats: O.0791 Inches Minimum And O.0806 Inches Maximum Shank Diameter: O.2016 Inches Minimum And O.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: O.295 Inches Minimum And O.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: O.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: Nominal Thread Size: O.190 Inches Shear Strength: Steel Comp Ed340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Classification: Surface Treatment: Cadmium Overall Oq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Orsell Treatment: Cadmium Overall Oq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Thread Direction: | Right-hand |
| Head Height: 0.045 Inches Minimum And 0.055 Inches Maximum Width Between Flats: 0.0791 Inches Minimum And 0.0806 Inches Maximum Shank Diameter: 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Fastener Length: | 0.503 Inches Minimum And 0.523 Inches Maximum |
| Width Between Flats: 0.0791 Inches Minimum And 0.0806 Inches Maximum 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Material: Material Document And Classification: Surface Treatment Document And Classification: Surface Treatment Document And Classification: Gup-416.ty 2,cl 2 Fed Spec Single Treatment Response Overall Ocentified Assimination 0.2016 Inches Maximum 0.2026 Inches Maximum 0.2056 Inches Maximum 0.2095 Inches Maximum | Head Style: | Err-090 |
| Shank Diameter: 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Head Height: | 0.045 Inches Minimum And 0.055 Inches Maximum |
| Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Width Between Flats: | 0.0791 Inches Minimum And 0.0806 Inches Maximum |
| Head Major Diameter: Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum 160000 Pounds Per Square Inch Nominal Thread Size: Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Cadmium Overall Surface Treatment Document And Classification: Classification: Cetyl Alcohol 0.193 Inches Maximum 0.193 Inches Maximum 0.193 Inches Maximum 0.194 Inches 0.190 Inches 0.19 | Shank Diameter: | 0.2016 Inches Minimum And 0.2026 Inches Maximum |
| Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Shank Style: | Pin-rivet, Straight, Threaded |
| Grip Length: O.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: O.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Gurface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Head Major Diameter: | 0.295 Inches Minimum And 0.315 Inches Maximum |
| Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 5hear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Lubrication: | Cetyl Alcohol |
| Minimum Tensile Strength: Nominal Thread Size: Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Grip Length: | 0.193 Inches Maximum |
| Nominal Thread Size: 5hear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Surface Treatment Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Thread Quantity Per Inch: | 32 |
| Shear Strength: 95000 Single Pounds Per Square Inch Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Classification: | Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Nominal Thread Size: | 0.190 Inches |
| Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Cadmium Overall Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Classification: | Shear Strength: | 95000 Single Pounds Per Square Inch |
| Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Material: | Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: Surface Treatment Document And Classification: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | Material Document And | |
| Surface Treatment Document And Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | | |
| Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall | | Cadinian Overan |
| Thread Series Designator: Unjf | Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| | Thread Series Designator: | Unjf |

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/BACB30FP6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/bin_rivets/BACB30FP6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/BACB30FP6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/BACB30FP6-3 and selecting the quantity you want then click "add to cart".