

Description

Fastener Length: 37/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACB30FQ6A4 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-451-7590 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N BACB30FQ6A4 Specifications

| | |
|---------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.565 Inches Minimum And 0.585 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.079 Inches Minimum And 0.080 Inches Maximum |
| Shank Diameter: | 0.201 Inches Nominal |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.305 Inches Nominal |
| Grip Length: | 0.245 Inches Minimum And 0.255 Inches Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Iron Alloy 660 Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30FQ6A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.